

FULL STRENGTH FORMULA

ORANGE ANTIFREEZE/ COOLANT



FULL STRENGTH FORMULA

FVP® Full Strength Orange Formula Antifreeze/Coolant can be used in place of Dex-Cool® coolant in all General Motors® cars and light duty trucks. FVP® Full Strength Orange Formula Antifreeze/Coolant is compatible and formulated for use with any antifreeze/coolant in any make or model of car or light duty truck and other engine metals. This formula has a concentrated blend of premium long-lasting inhibitors to offer protection for up to 5 years or 150,000 miles* against temperature extremes, the ravages of rust and corrosion, and premature water pump failure when used as directed. Available in gallons and 55 gallon drums.

*-DEX-COOL is a registered trademark of GM Corporation

- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.

Product specifications when used as directed:

- Meets ASTM D 3306, D4985
- May be added to the antifreeze/ coolant of ANY make and model of automobile and light duty truck on the road, foreign or domestic
- Protects aluminum and ANY other engine metals
- Meets GM and Ford performance specifications
- Compatible with orange OAT fluids

PRODUCT SIZES	
FVPDEX-GAL	1 gal. 6/case
FVPDEX-55GAL	55 gal drum



Composition by Volume

Ethylene Glycol 93.5%
Soluble Inhibitors (Anhydrous) 4.4%
Total Water 2.1%
Dyes (Orange) Trace

Properties

Color Orange

Odor Characteristic

Ash Content - ASTM D 1119 1.09% max

pH - 50% by Volume Solution - ASTM D 1287 8.7

Reserve Alkalinity - ASTM D 1121 5.5

Specific Gravity

at 20/20°C - 50% by Volume Solution - ASTM D 1122 1.0709

Freezing Point

40% by Volume Solution - ASTM D 1177 -12° F [-24 °C]

50% by Volume Solution - ASTM D 1177 -34° F [-37 °C]

60% by Volume Solution - ASTM D 1177 -62° F [-52 °C]

Boiling Point, under standard pressure

40% by Volume Solution - ASTM D 1120 223 °F [106 °C]

50% by Volume Solution - ASTM D 1120 227 °F [108 °C]

60% by Volume Solution - ASTM D 1120 232 °F [111 °C]

Flash Point (Tag Open Cup) 70% by Volume Solution None

Foam Test - ASTM D 1881 50 ml/1 sec

Average Net Weight/Gallon at 68°F [20°C] 9.3 lbs.

Typical Values

93.5%
4.4%
2.1%
Trace

Orange
Characteristic

1.09% max
8.7
5.5

1.0709

-12° F [-24 °C]
-34° F [-37 °C]
-62° F [-52 °C]

223 °F [106 °C]
227 °F [108 °C]
232 °F [111 °C]

None
50 ml/1 sec
9.3 lbs.

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORYMOTORPARTS™

WE SUPPLY YOUR SUCCESS.®