50/50 PREDILUTED FORMULA **MULTI-VEHICLE** ANTIFREEZE/ **COOLANT**



FVP® 50/50 Prediluted Multi-Vehicle Antifreeze/Coolant is recommended, compatible, and formulated for use with any antifreeze/coolant in any vehicle with aluminum and other engine metals. This formula has a concentrated blend of premium long-lasting inhibitors to guard against temperature extremes and ravages of rust, corrosion, and premature water pump failure. FVP® 50/50 Prediluted Multi-Vehicle Antifreeze/ Coolant is a 50/50 blend of antifreeze/coolant concentrate and demineralized water that provides extended life protection for cars and light-duty trucks up to 5 years or 150,000 miles* when added to any extended life coolant. Available in gallons and 55 gallon drums.

- *- Compatible with other extended life and conventional coolants.
- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.

Product specifications when used as directed:

- Meets ASTM D 3306, D4985
- May be added to the antifreeze/coolant of any make and model of automobile and light duty truck on the road, foreign or domestic
- May be added to any color antifreeze/coolant (color may change, but performance will not be affected)
- · Protects aluminum and any other engine metals
- Universally works with all fluid colors; all OAT, POAT, HOAT & IAT

PRODUCT SIZES			
FVPMV50/50-GAL	1 gal.	6/case	
FVPMV50/50-DRUM	55 gal	drum	





Composition by Volume Antifreeze/Coolant Total Water	Typical Values 51% 49%
Dyes (Yellow)	Trace
Properties	V/ 11
Color Odor	Yellow Characteristic
Ash Content - ASTM D 1119	.4% max
pH - 50% by Volume Solution - ASTM D 1287	8.7
Reserve Alkalinity - ASTM D 1121	1.0
Specific Gravity	
at 20/20°C - 50% by Volume Solution - ASTM D 1122	1.0694
Freezing Point	
50% by Volume Solution - ASTM D 1177	-34°F (-37°C)
Boiling Point, under standard pressure	
50% by Volume Solution - ASTM D 1120 Flash Point (Tag Open Cup) 70% by Volume Solution	227°F (108°C) None
Foam Test - ASTM D 1881	50 ml/2.2 sec
Average Net Weight/Gallon at 68°F (20°C)	8.9 lbs.

REACH FOR WHAT WORKS."

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



WE SUPPLY YOUR SUCCESS.