dexos1 Gen3 MOTOR OIL

FVP Full Synthetic dexos1™ Gen3 Motor Oils are made with full synthetic base stocks to meet the stricter volatility limits and fuel economy demands of the latest Turbocharged Gasoline Direct Injection (TGDI) engine designs. These engines require lubricants to provide:

- Protection against abrasive soot particles, which can contribute to increased engine wear
- Outstanding cooling properties, which fight off deposits
- Excellent pre-ignition protection to deter engine damage

FVP Full Synthetic dexos1TM Gen3 Motor Oils are specifically formulated to prevent low speed pre-ignition (LSPI4) using advanced additive technology to address all these new performance demands. These motor oils better protect today's engines with enhanced performance in the areas of wear, cleanliness, and fuel economy while providing excellent protection for extended drains and extreme service conditions.

Industry and OEM Applications

- GM dexos™1 Gen 3 licensed
- API SP, SN Plus and prior "S" categories
- ILSAC GF-6A, Resource Conserving
- Meets the requirements for FORD:
 - WSS-M2C961-A1 (5W-30)
 - WSS-M2C962-A1 (0W-20)

PRODUCT SIZES		
0W20FSDEXOS-5QT	4/ case	
5W30FSDEXOS-5QT	4/ case	





SAE GRADE	0W-20	5W-30
Viscosity @ 40°C, cSt	42.58	11.670
Viscosity @ 100°C, cSt	8.088	0
Viscosity Index	167	175
Specific Gravity at 60°F	0.8452	0.8467
Pour Point, °C	-42	-39
Cold Crank Simulator, cP	5,619 (-35°C)	4,180 (-30°C)
Color ASTM	L3.0	L3.0
Flash Point, °C	229	231
TBN, mg KOH/g	7.8	8.0
Noack Volatility, %	10.5	9.8
HTHS, cP	2.7	3.2

Always follow operator's manual for recommended viscosity grade and API service classification dexos1™ Gen3 is a registered trademark of General Motors, LLC.

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



WE SUPPLY YOUR SUCCESS.®